



## ***2024 CATALOG***





## HD-0102-4

### 1 X 2 MINI SPLITTER

- Power: 5V DC@1A, 50/60Hz, 5W
- Output Video: HDMI Signal
- Video Amplifier Bandwidth: 3.4Gbps/340MHz
- Interlaced Resolutions (50/60Hz): 480i, 576i, 1080i
- Progressive Resolutions (50/60Hz): 480p, 576p, 720p, 1080p, 4K@30Hz
- Size: 3" x 2" x 0.6" (75 x 48 x 15mm)



## HD-0104-4PC

### 1 X 4 SPLITTER

- Supports Full 3D and 4K@30Hz resolution
- Supports 340MHz/3.4Gbps per channel (10.2Gbps all channels)
- Supports 12bit per channel (36bit all channels) deep color
- Supports HDCP 1.4
- Supports uncompressed audio such as LPCM7.1, including DD 5.1 Cinema Sound and 7.1 Digital Theater Sound



## HD-0204-4

### 2 X 4 SWITCHER/SPLITTER

- Supports HDMI 1.4b
- Supports 3D
- Supports 4K resolution
- Supports 3Gbps data rate for tmbs clock up to 300MHz
- Supports 8/10/12bit deep color
- Supports AWG26 HDMI standard cable: when the resolution is 1080p and below, input up to 15 meters, output up to 15 meters; when the resolution is 4K, input up to 8 meters, output up to 8 meters.
- Support single high definition display for multiple sources, such as DVD Players and Satellite Receivers, Digital Projectors, A/V Receivers, Set Top Boxes.



## HD-0208-4K

### 2 X 8 SWITCHER/SPLITTER

- Supports 3D
- Supports 4K resolution
- Supports 3Gbps data rate for tmbs clock up to 300MHz
- Supports 8/10/12 bit deep color
- Standard AWG26 cable: When the resolution is 1080p or below, input is up to 10 meters, output is up to 15 meters; When the resolution is 4k, input is up to 5 meters, output is up to 15 meters.
- High input definition to multiple HD output signal which can be used for TV's, A/V receivers, Projectors and other similar products.



**HDMI™**  
 HIGH-DEFINITION MULTIMEDIA INTERFACE

**CONVERTERS / SPLITTERS**

## HD-40101R-04

**4 HDMI INPUT SELECTOR TO 1 HDMI OUTPUT**

- HDMI 2.0
- 6.0 Gbps per channel bandwidth
- Video resolutions up to 4K x 2K@60Hz YUV 4:4:4
- CEC Pass-through
- HDCP 2.2 and HDCP 1.4
- High Dynamic Range (HDR) Video
- Switching between HDMI Inputs can be done on the Button located on the Front Panel or by selecting with the remote control



## HD-MX0404-4K

**MATRIX 4X4**

- HDMI version: HDMI 2.0/HDCP2.0
- HDMI resolution: up to 4K/60Hz
- Video format: 8 / 10 / 12 bit deep color
- Audio format: DTS-HD / Dolby-true HD LPCM7.1 / DTS / Dolby-AC3 / DSD
- Max baud rate: 18Gbps
- Input cable distance: > 10m AWG24
- Output cable distance: > 10m AWG24
- HDMI Input: 4
- HDMI output: 4
- Max working current: 1.6A
- Power adapter format input: AC (50Hz, 60Hz) 100V-240V; Output: DC12V/2A
- Operation Temperature range: -15°C - +45°C
- Operating Humidity range: 5 to 90%RH (no Condensation)
- Dimension: 276 x 143 x 26 mm (10.9" x 5.6" x 1")
- Switching between HDMI inputs can be done on the Button located on the front panel or by selecting with the remote control


**Remote Control  
Included**

**AC / DC  
Adapter Included**



## CV-HMVGA

### HDMI TO VGA CONVERTER

- Allows Users with Existing Monitors with VGA to Connect their Devices Via HDMI Port. Besides Extracting Audio Out, it can also get Extra Power for Devices through Micro USB Port



## BL-HD-MIMAD

### MHL HDTV SMART ADAPTER

- Connect your MHL-Enabled Phone to your High Definition TV or Computer Monitor
- Requires Standard HDMI Cable and Micro USB Charging Cable
- Simply Add Plug between MHL Adapter and your Device as shown
- 5-pin to 11pin Adapter Plug allows you to use your MHL Smart Adapter with the Latest Galaxy and MHL Compatible Devices



**HDMI™**  
HIGH-DEFINITION MULTIMEDIA INTERFACE



**ADAPTERS**

### HM-2009

#### HDMI ADAPTER

- HDMI 19 pin male to HDMI 19 Pin Female Right Angle
- 24K Gold-Plated
- RoHS Compliant



### HM-2012

#### HDMI FEMALE ADAPTER

- Cable Coupler
- Allows you to Link Two HDMI Cables



### HM-2013

#### DVI-D MALE TO HDMI FEMALE ADAPTER

- High Definition Multimedia Interface for HDTV & Home Theater
- 24Kt Gold Plated Connectors for Optimum Signal Transfer
- Dual Link 24 + 1 Pin (DVI-D) to 19 Pin (HDMI) Digital Connectors



### HMA-HF-HM

#### HDMI SOCKET TO HDMI M-MINI PLUG

- Commonly Used for TVs and Digital Camcorders to Convert HDMI Cable Ends into a HDMI Mini Connector
- F Adapter



### HMBL-2012

#### HDMI FEMALE ADAPTER

- Cable Coupler
- Allows you to Link Two HDMI Cables
- Blister Packing



### HDC-USB-HDMI

#### VIDEO CAPTURE CARD

- HDMI resolution: Maximum input support 4K 3840 x 2160@30Hz
- Video input format: 8/10/12 bit color Deep
- Video output mode: YUV, JPEG
- Video output resolution: Maximum output resolution 1920 x 1080@30Hz
- Supports audio format: LPCM
- Product Size: 63x27x13(mm); Product weight: 40g
- Supports most acquisition software, such as VLC, OBS, Amcap, etc.
- Supports Windows, Android, Mac iOS, etc.
- When using standard AWG26 cable, the input transmission distance is up to 15 meters (1080P and below resolution)
- No external power supply required, small size and easy to carry





## HDB-VRCA-HDMI-I

### HDMI CONVERTER

- Upscale composite to full HD 1080p
- HDMI output is selectable 720p 50/60Hz
- Settings of input signal and output resolution is Auto-stored when powered on again
- 720p/1080p button to switch the resolution to 720p or 1080p
- Input: Composite x 1, L/R stereo audio x 1
- Output: HDMI x 1, DC x 1
- Dimensions: 61.5 x 55 x 20mm (2.42" x 2.17" X 0.79")
- Weight: 37.5g (0.1 Lbs)



## HDB-HDMI-VRCA

### MINI HDMI TO AV CONVERTER

- Hardware Conversion, Plug and Play, No Software Drivers
- Compatible HDMI 1.3
- Support NTSC and PAL Output Formats
- One HDMI Input, AV Output
  - A. Input Terminal: HDMI x 1 Input
  - B. Video Output terminal: VIDEO x 1 Output
  - C. Analog Audio Output Terminals: L / R x 1 Output AV Video Output: 480i, 576i (Optional) Audio Output: Left and Right Channels (L / R)



## HDCBL-0102

### HDMI MALE TO 2-FEMALE SPLITTER CABLE

- 7.9" (20cm)
- Home Theater Interconnects
- Digital Interface HDMI Audio & Video Cable
- High Definition Multimedia Interface is a New Digital, which will Bring you the Purest Picture and Sound
- Delivers Best High-Frequency Response for Optical Resolution Using Silver-Plated Conductor
- Maintains Stronger Signal that Yield Superior Sonic and Video Accuracy with Precision Formulated, Polyethylene Dielectric Material
- Isolated from Outside Noise for Superior Clarity with Quad-Shielding
- Reduces Cross Talk and Interference Using Impedance-Matched, Twisted-Pair Construction
- Protects against Wire Damage for Consistently High-Quality Audio & Video with Integrated Strain Relief



## HM-2000R

### HDMI REPEATER

- Extends high definition video and digital audio using a single box solution.
- Allows you to customize the HDMI cable to 35 M.
- Supports high definition video up to 1080P.



**HDMI™**  
HIGH-DEFINITION MULTIMEDIA INTERFACE



**CABLES**

### HMBL-2002-6RA

6' HDMI CABLE WITH FTR

- 4K Resolution Support
- Audio Return Channel (ARC) Support
- 4K Triple Shielded Oxygen Free
- 6' with Ferrite Core



### HMBL-2002-12RA

12' HDMI CABLE WITH FTR

- 4K Resolution Support
- Audio Return Channel (ARC) Support
- 4K Triple Shielded Oxygen Free
- 12' with Ferrite Core



### HMW-2005-6-4K

6' HDMI CABLE

- 4K Resolution
- Audio Return Channel (ARC) Support
- White Cable
- 1.4V



### HMW-2005-10-4K

10' HDMI CABLE

- 4K Resolution
- Audio Return Channel (ARC) Support
- White Cable
- 1.4V



### HMW-2005-15-4K

10' HDMI CABLE

- 4K Resolution
- Audio Return Channel (ARC) Support
- White Cable
- 1.4V





**HM-0005-6**

**HM-0005-12**

**HDMI CABLE**

- Available in 6' and 12'
- Economy Series
- 1.4V



**HMM-1005-6**

**MINI HDMI MALE TO  
HDMI MALE**

- 6'



**HMBL-2002-6-4K**

**HMBL-2002-12-4K**

**HDMI CABLE WITH FILTER**

- Gold Connectors
- Available in 6' and 12'
- 1.4V



**HM-2005-3-4K**

**HM-2005-6-4K**

**HM-2005-9-4K**

**HM-2005-12-4K**

**HM-2005-25-4K**

**HM-2005-50**

**HDMI CABLE**

- Gold Connectors
- Available in 3', 6', 9', 12', 25' and 50'
- 1.4V





**HDMI™**  
HIGH-DEFINITION MULTIMEDIA INTERFACE



**CABLES**

**HD-3D21R3-8K (3')**  
**HD-3D21R10-8K (10')**  
**HD-3D21R15-8K (15')**  
**HD-3D21R20-8K (20')**  
**HD-3D21R25-8K (25')**

**8K HIGH SPEED WITH  
ETHERNET HDMI CABLE**

- 24K Gold Plated Connectors
- Multi-Stranded Tinned Copper Conductor
- Quadruple Shielding



**HDMI® 2.1**  
HIGH-DEFINITION MULTIMEDIA INTERFACE



**HDD-3D21R25-8K (25')**  
**HDD-3D21R50-8K (50')**  
**HDD-3D21R75-8K (75')**  
**HDD-3D21R100-8K (100')**  
**HDD-3D21R150-8K (150')**

**8K HIGH SPEED WITH  
ETHERNET HDMI CABLE**

- 60Hz active optical fiber
- Optical fiber cable allows longer distances
- FULL HD 3D
- Supports YUV 4:4:4/60Hz
- Supports HDCP 2.3
- Audio return channel
- Additional color spaces
- 24K gold plated connectors

**Light and Fast with  
Optical Fiber Cable**



**HDMI® 2.1**  
HIGH-DEFINITION MULTIMEDIA INTERFACE



**HDM-3D20S25-4K (25')**

**HDM-3D20R50-4K (50')**

**HDM-3D20R75-4K (75')**

**HDM-3D20R100-4K (100')**

**4K HIGH SPEED WITH  
ETHERNET HDMI CABLE**

- 4K HDMI video resolution
- HDMI ethernet channel
- FULL HD 3D
- 99.99% Oxygen free bare copper
- 8Gbps transfer speed
- Audio return channel
- Additional color spaces
- 24K gold plated connectors
- Guarantee optimum EMI-free transmission
- Support Dolby True HD and DTS-HD



**With Repeater**



**APHI-FA4K-6 (6')**

**APHI-FA4K-12 (12')**

**12FT 4K HDMI CABLE**

- Latest HDMI 2.0 Version
- Compatible with most 3D formats, true 3D gaming and 3D home theater applications
- Ultra high-speed bandwidth up to 2200Mhz (18GBps)
- Audio return channel
- Supports 32-channel digital audio new formats as Dolby True HD, DTS-HD Master Audio
- Enable video resolution up to 4 times the Full HD: 3840x2160 at 24Hz/25Hz/30Hz, 4096x2160 at 24Hz at 50 to 60 fps
- Deep color from 24-bit to 30-bit, 36-bit, 12-bit (sYCC601 color, Adobe RGB color or Adobe YCC601)
- 4 times larger bandwidth for 4K than 1.4 HDMI
- 19-pin gold plated connectors for a higher speed and more accurate transmission
- Multiple-layer shielding prevents EMI (electromagnetic interference) and RFI (radio frequency interference) from ruining your digital picture
- Braided Nylon Jacket: durable and flexible nylon mesh jacket with environment friendly PVC double layer protection, this ensures a reliable protection of the outer jacket



**6' and 12'**





**HDM-3D14R-50-4K**

**HDM-3D14R-75-4K**

**HDM-3D14R-100-4K**

**HDMI CABLE WITH BUILT IN REPEATER**

- 4K Resolution Support
- 24K Gold-plated connectors
- Oxygen-Free Copper Conductor
- 3D Compatible
- 1.4V



**With Repeater**



*This HDMI Cable is directional, Please Note "INPUT" & "OUTPUT" Plug*







## APTOS-DF6

## APTOS-DF12

### DIGITAL TOSLINK AUDIO CABLE

- Fiber Optic Cable
- Connect your Audio System to your HDTV
- Premium Toslink Audio
- 24K Gold-Plated Connector
- Braided Nylon Jacket
- PMMA Fiber Core
- 6FT. & 12FT. Length



**24KT**  
Gold-Plated  
RCA Connectors

## OFC-3 (3")

## OFC-6 (6")

## OFC-12 (12")

## OFC-25 (25")

### OPTICAL FIBER CABLE

- 06mm optical cable, Toslink-Toslink plugs
- Gold-plated connectors for CD/VCD/DVD players to digital receivers
- Electromagnetic interference-free data link



## OFC-Y1-2

### DIGITAL SPDIF OPTICAL AUDIO SPLITTER

- Material: ABS Construction
- Usage: One output can be divide into dual interface outputs.
- Size: 57 x 40 x 20mm (2.24" x 1.57" x 0.79")
- Weight: 16g (0.035 lbs)
- Cables not included.





# HDMI™

HIGH-DEFINITION MULTIMEDIA INTERFACE



## CONVERTERS / ADAPTERS

### CV-MUSBC5

**USB 2.0 MALE TO RJ45 FEMALE ETHERNET 10/100 MBPS NETWORK LAN ADAPTER CABLE FOR APPLE MACBOOK, LENOVO, THINKPAD, DELL, SONY, SAMSUNG, ACER, ASUS, AND OTHER LAPTOP BRANDS**

- USB 2.0 A to Ethernet Port Adapter
- Enables Internet Connection Via USB Port
- Powered by USB Port, No External Power Adapter Required
- Half/Full Duplex 10/100 Mbps Operation
- Self-Adapting 10 Mbps or 100 Mbps Network Adapter
- Compliant to USB Interface Version 1.0/1.1/2.0
- Compatible with Windows 98SE ME/2000/2003/XP/Vista/Windows 7



### CV-HDIDSP

**HDMI FEMALE TO DISPLAYPORT MALE ADAPTER**

HDMI Adapter to DisplayPort allows for transmission of both audio and video from a supported device to a monitor, HDTV, projector or any other device with DisplayPort.

It supports up to 4K resolution as well as Audio Return Channel (ARC) to manage additional audio devices, such as audio bars, through a single cable.

- 4K Resolution support
- Audio Return Channel (ARC) support



### CV-C5RCA

**AUDIO EXTENDER/CONVERTER**

- Male Stereo RCA to RJ45 Adapter
- Length: 13"
- Audio Balun
- RCA Stereo Audio Extender Converter Over Cat5 or Cat6





## HDC-HDMI35

### HD VIDEO AUDIO CONVERTER

- No Need to Install Drivers
- Portable, Flexible, Plug and Play
- Low Power No Need for a Power Supply
- Output the Audio Synchronized with Video
- High Output Bandwidth, Capable of Supporting 3840 x 2160 @ 30Hz



## HD-ARC-EXT2

### HDTV + AUDIO & ARC

- HDMI Audio splitter with ARC support, stereo and surround sound options
- Supports 4K x 2K@60Hz, Supports 3D
- Digital audio format: Digital theater sound-HD/DD 5.1 cinema sound/7.1 Digital Theater Sound HDMI Resolution: 4Kx2K / 3D / 1080P / 720P / 576P / 480P / 480i
- Supports video color format: 24bit/deep color 30bit, 36bit
- Max bandwidth: 600MHZ
- Max baud rate: 18Gbps
- Includes 3.3Ft/1M optical cable





## HD-DIGI-ANA

### HD VIDEO PROCESSING

- Converts S/PDIF or Optical (Toslink) to Analog R/L Audio Signal
- Supports 2 Channels LPCM Digital Audio Only
- Supports Sampling Rate at 32, 44.1, 48 and 96KHz
- Input: S/PDIF x 1, Toslink x 1
- Output: L/R Audio x 1, 3.5mm Audio x 1
- Dimensions: 76 x 56 x 22mm
- Weight: 47g



## HD-DIGI-ANAD

### DIGITAL TO ANALOG CONVERTER

- Converts S/PDIF or Optical (Toslink) to Analog R/L Audio Signal
- Supports 2 Channels LPCM Digital Audio Only
- Supports Sampling Rate at 32, 44.1, 48 and 96KHz
- Input: S/PDIF x 1, Toslink x 1
- Output: L/R Audio x 1, 3.5mm Audio x 1
- Dimensions: 76 x 56 x 22mm (2.99" x 2.20" x 0.87")
- Weight: 47g (0.1 Lbs)
- Built-In Conversion Module for Movies with Enhanced Sound Programming



## HD-EX250SR


### HDMI IP EXTENDER OVER SINGLE CAT5E/6

#### Extra long range and Power regulator


- Power Supply: 2x 5V DC/1A
- Supports Resolutions: 480i/60Hz, 480p/60Hz, 576i/50Hz, 560p/50Hz, 720p/50/60Hz, 1080i/50/60Hz, 1080p/50/60Hz
- Working Temperature: -10°C~60°C
- Link Connector (Sender/Receiver): UTP/STP CAT5e/6
- Power Consumption: 3W (Max) Each
- Relative Humidity: 20%~90%
- Dimensions: 4.3"x2.3"x1.0" (110x58x26mm)
- Weight: 0.53Lbs (0.239Kg)



### SENDER / RECEIVER



**ROUTER CONNECTION**



**LAN CONNECTION**

