


2024 CATALOG





CAR SPEAKERS

XGT-1402

4" 2-WAY IMPP CONE COAXIAL CAR SPEAKER

- 100 Watts (P.M.P.O.)
- 50 Watts (R.M.S.)
- Frequency Response: 80Hz~18KHz
- Sensitivity: 88dB / W(1M)
- Impedance: 4 Ohm

4"

100 Watts



XGT-1502

5-1/4" 2-WAY IMPP CONE COAXIAL CAR SPEAKER

- 200 Watts (P.M.P.O.)
- 100 Watts (R.M.S.)
- Frequency Response: 75Hz~18KHz
- Sensitivity: 89dB / W(1M)
- Impedance: 4 Ohm

5-1/4"

200 Watts



XGT-1602

6" 2-WAY IMPP CONE COAXIAL CAR SPEAKER


- 300 Watts (P.M.P.O.)
- 150 Watts (R.M.S.)
- Frequency Response: 70Hz~18KHz
- Sensitivity: 89dB / W(1M)
- Impedance: 4 Ohm

6"/6.5"

300 Watts



Universal 6" / 6.5" Basket



CAR SPEAKERS

XGT-1600

6" DUAL CONE IMPP CONE CAR SPEAKER

- 150Watts (P.M.P.O.)
- 75Watts (R.M.S.)
- Frequency Response: 70Hz~15KHz
- Sensitivity: 89dB / W(1M)
- Impedance: 4 Ohm

6"/6.5"

150 Watts



XGT-1603

6" 2-WAY IMP CONE COAXIAL CAR SPEAKER

- 350Watts (P.M.P.O.)
- 175Watts (R.M.S.)
- Frequency Response: 70Hz~18KHz
- Sensitivity: 89dB / W(1M)
- Impedance: 4 Ohm

6"/6.5"

350 Watts



Universal 6" / 6.5" Basket

XGT-1605


5-1/2" DUAL CONE CAR SPEAKER

- 60Watts (P.M.P.O.)
- 30Watts (R.M.S.)
- Frequency Response: 150Hz~12KHz
- Sensitivity: 90dB / W(1M)
- Impedance: 4 Ohm

5-1/2 In

60 Watts





XGT-6803

6" X 8" 3-WAY IMPP CONE TRIAXIAL CAR SPEAKER

- 350 Watts (P.M.P.O.)
- 175 Watts (R.M.S.)
- Frequency Response: 70Hz~20KHz
- Sensitivity: 89dB / W(1M)
- Impedance: 4 Ohm

350 Watts



XGT-6903

6" X 9" 3-WAY IMPP CONE TRIAXIAL CAR SPEAKER

- 400 Watts (P.M.P.O.)
- 200 Watts (R.M.S.)
- Frequency Response: 60Hz~18KHz
- Sensitivity: 90dB / W(1M)
- Impedance: 4 Ohm

400 Watts



XGT-6904

6" X 9" 4-WAY IMPP CONE QUAD-AXIAL CAR SPEAKER

- 500 Watts (P.M.P.O.)
- 250 Watts (R.M.S.)
- Frequency Response: 60Hz~18KHz
- Sensitivity: 90dB / W(1M)
- Impedance: 4 Ohm

500 Watts





CAR SPEAKERS

XFG-1603

6" 3-WAY IMPP CONE TRIAXIAL CAR SPEAKER

Universal 6" / 6.5" Basket

- 300Watts (P.M.P.O.)
- 150Watts (R.M.S.)
- Frequency Response: 90Hz~18KHz
- Sensitivity: 86dB/W(IM)
- Impedance: 4 Ohm

6"/6.5"

300 Watts



XFG-6903


6" X 9" 3-WAY IMPP CONE TRIAXIAL CAR SPEAKER

- 350Watts (P.M.P.O.)
- 175Watts (R.M.S.)
- Frequency Response: 55Hz~18KHz
- Sensitivity: 87dB/W(IM)
- Impedance: 4 Ohm

6x9 In

350 Watts





XTC-3300

SUPER HIGH -FREQUENCY MINI TWEETER

- 500 Watts
- Frequency Response: 5KHz~20KHz
- Sensitivity: 97dB
- Output Power: 160 Watts



500 Watts

XTC-5500

SUPER HIGH -FREQUENCY MINI TWEETER

- 500 Watts
- Frequency Response: 5KHz~20KHz
- Sensitivity: 100dB
- Output Power: 120 Watts



500 Watts


XTC-7700

SUPER HIGH -FREQUENCY MINI TWEETER

- 600 Watts
- Frequency Response: 5KHz~20KHz
- Sensitivity: 100dB
- Impedance: 4 Ohm



600 Watts



SPEAKER BOXES

KIC-80

DUAL 8" WOOFER ENCLOSURE

- 2" x 5" Piezo Tweeters (2 Pcs.)
- Carpet Finish
- Impedance: 4 Ohms
- Frequency Response: 45Hz-20KHz
- Sensitivity: 88dB (1W/ 1M)
- Size: 11-3/5" x 27-1/2" x 7-1/2"
- Weight: 17.5 LBS.
- Peak Power: 250 Watt

GREAT FOR HATCHBACK & SINGLE CAB PICKUP TRUCKS



250 WATTS

KIC-100

DUAL 10" WOOFER ENCLOSURE

- 2" x 5" Piezo Tweeters (2 Pcs.)
- Carpet Finish
- Impedance: 4 Ohms
- Frequency Response: 40Hz-20KHz
- Sensitivity: 89dB (1W/ 1M)
- Size: 12-3/5" x 29-1/2" x 8"
- Weight: 36 lbs.
- Peak Power: 250 Watt

GREAT FOR HATCHBACK & SINGLE CAB PICKUP TRUCKS



250 Watts

KIC-120


DUAL 12" WOOFER ENCLOSURE

- 2" x 5" Piezo Tweeters (2 Pcs.)
- Carpet Finish
- Impedance: 4 Ohms
- Frequency Response: 35Hz-20KHz
- Sensitivity: 88dB (1W/ 1M)
- Size: 15-1/8" x 33" x 8"
- Weight: 28.5 lbs.
- Peak Power: 500 Watt

GREAT FOR HATCHBACK & SINGLE CAB PICKUP TRUCKS



500 Watts



SPEAKER BOX KITS / POWER PRODUCTS

XEQ-700

SLIM MOUNT EQUALIZER 5 BAND

- Frequency Response: 20Hz~20KHz
- Pre Graphic Frequency: 40Hz, 200Hz, 200Hz, 2KHz, 20KHz
- Total Harmonic Distortion(TDH): 0.05%
- Signal-to-noise Ratio: >80dB
- Inputs: Switchable to Ratio or Aux
- Equalization Boost/Cut: ±12dB
- Subwoofer Crossover Frequency: Selectable 80 or 120Hz
- Channel Separation: 70dB
- Maximum Output Voltage: 9V RMS
- Power Supply: 11~15V Negative Ground
- Fuse: 1A(AGC type)
- Dimensions: Chassis 6.75" x 1.125" x 4.25"
- Mounting Depth: 4.5"(Including RCA Jacks)



9V

XMOTO-200

2 CHANNEL MINI AMPLIFIER

- Max Power: 200W Max
- RMS Power: 2 x 25W @ 4Ω
- Frequency Response: 20Hz~20KHz
- Signal Noise Ratio: 90dB
- Output Impedance: 4Ω
- DC Power: 211.5~14.4V
- THD: <1.3%
- Dimensions: 4.3" x 3.1" x 1.6" (110 x 80 x 40mm)
- RCA Input/High Input
- Remote turn On/Off
- Easy to connect
- 3.5mm Plug Input



XCAP-2000

POWER CAPACITOR

- VCD: 20 Max, 24V Surge
- ESR: 0.002 Ω or less
- Terminals: 1/4~28 Thread
- Digital Display & Status Indicator
- Digital Electronic Protection

2 FARAD



XCAP-3500

POWER CAPACITOR

- VCD: 20 Max, 24V Surge
- ESR: 0.002 Ω or less
- Terminals: 1/4~28 Thread
- Digital Display & Status Indicator
- Digital Electronic Protection

3.5 FARAD



XTM-200

2 CHANNEL IC AMPLIFIER

- Power: 200W Max @ 4Ω Mono
- Frequency Response: 20Hz~20KHz
- Variable Bass Boost: 0~12dB @ 45Hz
- Channel Separation: 60dB
- Signal Noise Ratio: 90dB
- Input Impedance: 22KΩ
- Input Sensitivity: 200mV~6V
- THD: <0.05%
- Dimensions: 4.3" x 5.9" x 2" (110x150x50mm)



XTM-400

4 CHANNEL IC AMPLIFIER

- Power: 400W Max @ 4Ω Stereo
- Frequency Response: 20Hz~20KHz
- Selectable Crossover: LPF, FULL
- Channel Separation: 60dB
- Signal Noise Ratio: 90dB
- Input Impedance: 22KΩ
- Input Sensitivity: 200mV~6V
- THD: <0.05%
- Dimensions: 4.3" x 5.9" x 2" (110x150x50mm)

